

[Products > IP65 Batten > IP65 Batten 1003.1014](#)

IP65 Batten 1003.1014

Line Drawing



Downloads



Physical Specification

Code	1003.1014.01	1003.1014.02	1003.1014.03
Product Dimensions (mm)	L580×W53×H34mm	L1180×W53×H34mm	L1480×W53×H34mm
Finish/Color	Opal +Gloss White	Opal +Gloss White	Opal +Gloss White
Material	PC	PC	PC
On/Off Switch	N	N	N
Cable Length (m)	N	N	N
Cable Spec.	N	N	N
Plug	N	N	N
Terminal Block	quick fit	quick fit	quick fit
Accessories	screw,expansion bolts,fixing brackets	screw,expansion bolts,fixing brackets	screw,expansion bolts,fixing brackets
Installation	Surface mounted	Surface mounted	Surface mounted
Class	2	2	2

Electrical Characteristics

Code	1003.1014.01	1003.1014.02	1003.1014.03
Total Power Consumption Wattage/On-Mode Power	10	22	24
Product Voltage	220-240	220-240	220-240
Hertz	50/60	50/60	50/60
IP Rating	IP65	IP65	IP65
Luminous Flux	1150	2530	2750
Kelvin	3000K/4000K/6000K	3000K/4000K/6000K	3000K/4000K/6000K
LED Package Type	SMD	SMD	SMD
Lamp/Bulb Specification (if not LED)	N/A	N/A	N/A
Lamp/Bulb included?	N/A	N/A	N/A
SDCM	<6	<6	<6
CRI	>80	>80	>80
Power Factor	>0.5	>0.5	>0.5
UGR	>19	>19	>19

Function

Code	1003.1014.01	1003.1014.02	1003.1014.03
Linkable	Optional	Optional	Optional
CCT function	N	N	N
Multi-section Power	N	N	N
Dimmable	N	N	N
Sensor	N	N	N
Emergency	N	N	N
Battery Spec.	N/A	N/A	N/A
Others (Solar etc...)	power cable is optional	power cable is optional	power cable is optional

ABOUT US

[Introduction](#)
[Research And Development](#)
[Technical Department](#)
[Graphics Department](#)
[Qualification](#)

PRODUCT

[New arrival](#)
[Waterproof](#)
[Bulkhead / Flush](#)
[Ceiling light](#)
[Desk lamp](#)
[Battens](#)
[Panel / Frame](#)
[Downlight](#)
[Counter & Cabinet](#)
[Work light & Flood light](#)

CONTACT

Email:reon@brightsources.cn
Phone:+86-574-87309279
Fax:+86 574 8730 3683