


[Products](#) > [IP65 Batten](#) > [IP65 Batten 1003.1012](#)

IP65 Batten 1003.1012

Line Drawing



Downloads



Physical Specification

Code	1003.1012.01	1003.1012.02	1003.1012.03
Product Dimensions (mm)	L590×W72×H61mm	L1180×W72×H61mm	L1480×W72×H61mm
Finish/Color	Grey+Opal finished	Grey+Opal finished	Grey+Opal finished
Material	PC+Iron	PC+Iron	PC+Iron
On/Off Switch	N	N	N
Cable Length (m)	N	N	N
Cable Spec.	N	N	N
Plug	N	N	N
Terminal Block	quick fit	quick fit	quick fit
Accessories	screw,expansion bolts,fixing brackets	screw,expansion bolts,fixing brackets	screw,expansion bolts,fixing brackets
Installation	Surface mounted	Surface mounted	Surface mounted
Class	1	1	1

Electrical Characteristics

Code	1003.1012.01	1003.1012.02	1003.1012.03
Total Power Consumption Wattage/On-Mode Power	12	24	33
Product Voltage	220-240	220-240	220-240
Hertz	50/60	50/60	50/60
IP Rating	IP65	IP65	IP65
Luminous Flux	1560	3120	4300
Kelvin	3000K/4000K/6000K	3000K/4000K/6000K	3000K/4000K/6000K
LED Package Type	SMD	SMD	SMD
Lamp/Bulb Specification (if not LED)	N/A	N/A	N/A
Lamp/Bulb included?	N/A	N/A	N/A
SDCM	<6	<6	<6
CRI	>80	>80	>80
Power Factor	>0.5	>0.5	>0.9
UGR	>19	>19	>19

Function

Code	1003.1012.01	1003.1012.02	1003.1012.03
Linkable	Y	Y	Y
CCT function	Optional	Optional	Optional
Multi-section Power	Optional	Optional	Optional
Dimmable	Optional	Optional	Optional
Sensor	Optional	Optional	Optional
Emergency	Optional	Optional	Optional
Battery Spec.	N/A	N/A	N/A

ABOUT US

[Introduction](#)
[Research And Development](#)
[Technical Department](#)
[Graphics Department](#)
[Qualification](#)

PRODUCT

[New arrival](#)
[Waterproof](#)
[Bulkhead / Flush](#)
[Ceiling light](#)
[Desk lamp](#)
[Battens](#)
[Panel / Frame](#)
[Downlight](#)
[Counter & Cabinet](#)
[Work light & Flood light](#)

CONTACT

Email:reon@brightsources.cn
[Phone:+86-574-87309279](tel:+86-574-87309279)
[Fax:+86 574 8730 3683](tel:+86-574-8730-3683)