


[Products](#) > [IP65 Batten](#) > [IP65 Batten 1003.1020](#)

IP65 Batten 1003.1020

Line Drawing



Downloads



Physical Specification

Code	1003.1020.01	1003.1020.02	1003.1020.03	1003.1020.04
Product Dimensions (mm)	L545×W43×H47mm	L1145×W43×H47mm	L1445×W43×H47mm	L1745×W43×H47mm
Finish/Color	Opal +Gloss White	Opal +Gloss White	Opal +Gloss White	Opal +Gloss White
Material	PC	PC	PC	PC
On/Off Switch	N	N	N	N
Cable Length (m)	N	N	N	N
Cable Spec.	N	N	N	N
Plug	N	N	N	N
Terminal Block	quick fit	quick fit	quick fit	quick fit
Accessories	screw,expansion bolts,fixing brackets	screw,expansion bolts,fixing brackets	screw,expansion bolts,fixing brackets	screw,expansion bolts,fixing brackets
Installation	Surface mounted	Surface mounted	Surface mounted	Surface mounted
Class	2	2	2	2

Electrical Characteristics

Code	1003.1020.01	1003.1020.02	1003.1020.03	1003.1020.04
Total Power Consumption Wattage/On-Mode Power	18	36	45	60
Product Voltage	220-240	220-240	220-240	220-240
Hertz	50/60	50/60	50/60	50/60
IP Rating	IP65	IP65	IP65	IP65
Luminous Flux	1800	3780	4950	6600
Kelvin	2700K/3000K/4000K/5000K/6500K			
LED Package Type	SMD	SMD	SMD	SMD
LPW@4000K	100-110lm/W			
Lamp/Bulb Specification (if not LED)	N/A	N/A	N/A	N/A
Lamp/Bulb included?	N/A	N/A	N/A	N/A
SDCM	<6	<6	<6	<6
CRI	>80	>80	>80	>80
Power Factor	>0.5	>0.9	>0.9	>0.9
UGR	>19	>19	>19	>19

Function

Code	1003.1020.01	1003.1020.02	1003.1020.03	1003.1020.04
Linkable	Y	Y	Y	Y
CCT function	Optional	Optional	Optional	Optional
Multi-section Power	Optional	Optional	Optional	Optional
Dimmable	Optional	Optional	Optional	Optional
Sensor	Optional	Optional	Optional	Optional
Emergency	Optional	Optional	Optional	Optional
Battery Spec.	N/A	N/A	N/A	N/A

ABOUT US

Introduction
Research And Development
Technical Department
Graphics Department
Qualification

PRODUCT

New arrival
Waterproof
Bulkhead / Flush
Ceiling light
Desk lamp

Battens
Panel / Frame
Downlight
Counter & Cabinet
Work light & Flood light

CONTACT

Email:reon@brightsources.cn
Phone:+86-574-87309279
Fax:+86 574 8730 3683