


[Products](#) > [IP65 Batten](#) > [IP65 Batten 1003.1021](#)

IP65 Batten 1003.1021

Line Drawing



Downloads



Physical Specification

Code	1003.1021.01	1003.1021.02	1003.1021.03
Product Dimensions (mm)	L605×W47.5×H59.5mm	L1205×W43×H47mm	L1505×W43×H47mm
Finish/Color	Opal +Gloss White	Opal +Gloss White	Opal +Gloss White
Material	PC	PC	PC
On/Off Switch	N	N	N
Cable Length (m)	N	N	N
Cable Spec.	N	N	N
Plug	N	N	N
Terminal Block	quick fit	quick fit	quick fit
Accessories	screw,expansion bolts,fixing brackets	screw,expansion bolts,fixing brackets	screw,expansion bolts,fixing brackets
Installation	Surface mounted	Surface mounted	Surface mounted
Class	2	2	2

Electrical Characteristics

Code	1003.1021.01	1003.1021.02	1003.1021.03
Total Power Consumption Wattage/On-Mode Power	18	36	45
Product Voltage	220-240	220-240	220-240
Hertz	50/60	50/60	50/60
IP Rating	IP65	IP65	IP65
Luminous Flux	2160	4320	5400
Kelvin	2700K/3000K/4000K/5000K/6500K		
LED Package Type	SMD	SMD	SMD
LPW@4000K	120lm/W		
Lamp/Bulb Specification (if not LED)	N/A	N/A	N/A
Lamp/Bulb included?	N/A	N/A	N/A
SDCM	<6	<6	<6
CRI	>80	>80	>80
Power Factor	>0.5	>0.9	>0.9
Beam Angle	120°		
UGR	>19	>19	>19

Function

Code	1003.1021.01	1003.1021.02	1003.1021.03
Linkable	Y	Y	Y
CCT function	Optional	Optional	Optional
Multi-section Power	Optional	Optional	Optional
Dimmable	Optional	Optional	Optional
Sensor	Optional	Optional	Optional
Emergency	Optional	Optional	Optional
Battery Spec.	N/A	N/A	N/A

ABOUT US

[Introduction](#)
[Research And Development](#)
[Technical Department](#)
[Graphics Department](#)
[Qualification](#)

PRODUCT

[New arrival](#)
[Waterproof](#)
[Bulkhead / Flush](#)
[Ceiling light](#)
[Desk lamp](#)

[Battens](#)
[Panel / Frame](#)
[Downlight](#)
[Counter & Cabinet](#)
[Work light & Flood light](#)

CONTACT

Email:reon@brightsources.cn
[Phone:+86-574-87309279](tel:+86-574-87309279)
[Fax:+86-574-8730-3683](tel:+86-574-8730-3683)